



24

CE DoP 705

Declaration of Performance

Regulation (EU) Nr. 305/2011

Decorative wall slimline

- | | | |
|---|---|--|
| 1 | Harmonised technical standard | DIN EN 13986:2004+A1:2015 |
| 2 | Usage | Coated wood-based material for interior use as a non-load-bearing component in dry areas |
| 3 | Manufacturer | akustikplus GmbH & Co. KG, Postfach 100353, D-83003 Rosenheim |
| 4 | Assessment and verification of constancy of performance | System 3 ^{*)} |

Technical class	MDF according to EN 622-5
Panel thickness	16 - 19mm
Open area	≤ 34,5%

5 Essential characteristics**Declared performance**

Reaction to fire ^{*)}	EN 13501-1	Cs2 d0
Emission fo formaldehyde ^{*)}	EN 717-1/-2	E1
Pentachlorphenol content	EN 13986 - Kap. 5.18	≤ 5 ppm
Biological durability	EN 335	Class 1
Transverse tensile strength	EN 319	> 1,0 N/mm ²
Bending strength	EN 310	> 25 N/mm ²
Water vapour permeability	EN 13986 - Tab. 9	NPD
Airborne sound insulation	EN 13986 - Kap. 5.10	NPD
Sound absorption	EN 13986 - Tab. 10	NPD
Thermal conductivity	EN 13986 - Tab. 11	NPD

The performance of the product identified in (2) is in conformity with the declared performance in (5). This declaration of performance is issued under the sole responsibility of the manufacturer (3).

Signed for and on behalf of the manufacturer

Michael Paringer,
Managing Director Technology

Stephanskirchen, 14.02.2024

^{*)} In accordance with the harmonised standard specified in (1), the inspection body/bodies NB 1322 IBS Linz, NB 0766 EPH Dresden has/have performed type testing according to the system specified in (4).